

**HAMMER
TIME
DEMOLITION HIRE**

Product Catalogue



**HAMMERTIME
DEMOLITION HIRE**





**HAMMERTIME
DEMOLITION HIRE**

Welcome to **Hammertime Demolition Hire**, your premier source for high-quality paving breakers, jackhammers/chipping hammers, and a wide variety of mining tools. We specialize in providing top-of-the-line equipment for construction and mining professionals.


At **Hammertime Demolition Hire**, we understand the importance of having reliable and efficient equipment for your projects. That's why we offer a vast selection of paving breakers, jackhammers/chipping hammers, and other essential tools from the industry's leading brands. Whether you need equipment for **demolition, concrete removal, or rock excavation**, we have the right tools to get the job done.

Our experienced staff is always available to help you select the best tools for your needs, and we are committed to providing exceptional customer service at every stage of your project.

We also supply all types of mining tools, including rock drills, larger pneumatic breakers, and **much more**.

Hammertime Demolition Hire is dedicated to helping our customers achieve success in their projects.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE



Excellence

Our commitment to **excellence** is evident in everything we do. From the quality of our products to the level of customer service we provide, we strive to exceed expectations at every turn. You can trust us to deliver nothing but the **best**.

Professionalism

At our company, **professionalism** is key. We understand the importance of conducting business with integrity and respect, and we always strive to maintain the highest standards of professionalism in everything we do. When you work with us, you can expect a level of **professionalism** that is second to none.

Expertise

With years of experience under our belt, we have the **expertise** needed to tackle, even the most challenging projects. Our team has the knowledge and know-how to deliver outstanding results, no matter what. When you choose us, you can **trust** that you are in good hands.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

Paving Breaker

HDH 1210 S

Weight	20 kg [44 lb]
Length	609 mm [24"]
Blows per minute	1450
Air consumption	23 l/s [48 cfm]
Shank (standard)	25 x 108 mm
Retainer type	Latch



HDH 1230 S

Weight	30 kg [66 lb]
Length	660 mm [26"]
Blows per minute	1350
Air consumption	30 l/s [64 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 117 S

Weight	37 kg [81 lb]
Length	710 mm [28"]
Blows per minute	1200
Air consumption	35 l/s [74 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Spring



HDH 1240 S

Weight	40 kg [88 lb]
Length	718 mm [28.25"]
Blows per minute	1250
Air consumption	38 l/s [81 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 117L S

Weight	41 kg [91 lb]
Length	710 mm [28"]
Blows per minute	1200
Air consumption	35 l/s [74 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



RMT 0112

Weight	14.5 kg [32 lb]
Length	535 mm [21"]
Blows per minute	1620
Air consumption	23 l/s [49 cfm]
Shank (standard)	25 x 108 mm
Retainer type	Latch



HDH 0112 EXT

Weight	16 kg [35 lb]
Length	800 mm [31.5"]
Blows per minute	1620
Air consumption	23 l/s [49 cfm]
Shank (standard)	25 x 108 mm
Retainer type	Latch



HDH 20 PS

Weight	20 kg [44 lb]
Length	635 mm [25"]
Blows per minute	1140
Air consumption	25 l/s [53 cfm]
Shank (standard)	25 x 108 mm
Retainer type	Latch



HDH 1210 SVR

Weight	24.5 kg [55 lb]
Length	600 mm [24"]
Blows per minute	1400
Air consumption	26.5 l/s [56 cfm]
Shank (standard)	25 x 108 mm
Shank (option 1)	28 x 160 mm
Shank (option 2)	32 x 160 mm
Retainer type	Latch



HDH RTEX

Weight	25 kg [55 lb]
Length	780 mm [31"]
Blows per minute	870
Air consumption	18.5 l/s [39.2 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Lock retainer



HDH P60

Weight	33 kg [73 lb]
Length	690 mm [27.2"]
Blows per minute	1500
Air consumption	36 l/s [76 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 1260

Weight	31 kg [68 lb]
Length	680 mm [26.7"]
Blows per minute	1300
Air consumption	34.5 l/s [73 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 1260 SVR

Weight	34 kg [75 lb]
Length	735 mm [29"]
Blows per minute	1300
Air consumption	34.5 l/s [73 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 37P

Weight	37 kg [81 lb]
Length	729 mm [29"]
Blows per minute	1200
Air consumption	35 l/s [74 cfm]
Shank (standard)	32 x 160 mm
Retainer type	Latch



HDH 1290

Weight	39 kg [86 lb]
Length	730 mm [29"]
Blows per minute	1100
Air consumption	43 l/s [91 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH 1290 SVR

Weight	43.5 kg [96 lb]
Length	785 mm [31"]
Blows per minute	1300
Air consumption	43 l/s [91 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



HDH P90

Weight	43 kg [95 lb]
Length	710 mm [28"]
Blows per minute	1260
Air consumption	40 l/s [85 cfm]
Shank (standard)	32 x 160 mm
Shank (option)	28 x 160 mm
Retainer type	Latch



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



Chipping Hammer & 4 Bolt Chipping Hammer

HDH 4123 2H/2R

Weight	7 kg [15 lb]
Length	375 mm [14.8"]
Blows per minute	2500
Air consumption	14 l/s [30 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4123 3H/3R

Weight	8 kg [17.65 lb]
Length	426 mm [16.75"]
Blows per minute	2050
Air consumption	14 l/s [30 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4123 4H/4H

Weight	8.65 kg [19 lb]
Length	460 mm [18.1"]
Blows per minute	1600
Air consumption	14 l/s [30 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4125 2H/2R

Weight	7 kg [15.4 lb]
Length	380 mm [15"]
Blows per minute	2100
Air consumption	15.5 l/s [33 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4125 3H/3R

Weight	7.6 kg [16.75 lb]
Length	430 mm [17"]
Blows per minute	1650
Air consumption	16 l/s [34 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4125 4H/4R

Weight	8.4 kg [18.5 lb]
Length	455 mm [19"]
Blows per minute	1375
Air consumption	16.5 l/s [35 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 73

Weight	8.5 kg [19 lb]
Length	460 mm [18.11"]
Blows per minute	1650
Air consumption	18 l/s [38 cfm]
Shank (Round)	23 x 14 mm
Retainer type	Screw cap



HDH 66

Weight	5.50 kg [12 lb]
Length	430 mm [16.9"]
Blows per minute	2000
Shank (Round)	21 x 12 mm
Body	22 mm
Retainer Type	Screw Cap



HDH K13

Weight	13.3 kg [29.4 lb]
Length	525 mm [21"]
Blows per minute	1910
Air consumption	19 l/s [40 cfm]
Shank (Dia)	26 x 70 mm
Retainer type	Screw cap



HDH 03 PS

Weight	4 kg [8.8 lb]
Length	300 mm [11.8"]
Blows per minute	4080
Air consumption	6.9 l/s [15 cfm]
Shank (Hex)	19 x 50 mm
Retainer type	Screw cap



HDH 05 P

Weight	5.5 kg [12.1 lb]
Length	380 mm [15"]
Blows per minute	2760
Air consumption	9.5 l/s [0.34 cfm]
Shank (Hex)	19 x 50 mm
Retainer type	Screw cap



HDH 0017 SVR

Weight	9.5 kg [21 lb]
Length	540 mm [21"]
Blows per minute	1770
Air consumption	17 l/s [36 cfm]
Shank (Hex)	19 x 50 mm
Retainer type	Screw cap



HDH 0012

Weight	5.5 kg [12 lb]
Length	406 mm [16"]
Blows per minute	2580
Air consumption	9.5 l/s [20 cfm]
Shank (Hex)	19 x 50 mm
Retainer type	Screw type



HDH 4130 2H/2R

Weight	8.4 kg [18.5 lb]
Length	356 mm [14"]
Blows per minute	3600
Air consumption	14 l/s [30 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4130 3H/3R

Weight	9 kg [20 lb]
Length	387 mm [15.25"]
Blows per minute	2280
Air consumption	15.5 l/s [33 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4130 4H/4R

Weight	9.4 kg [21 lb]
Length	419 mm [16.50"]
Blows per minute	1800
Air consumption	16 l/s [34 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Spring



HDH 4131 3H/3R

Weight	8.5 kg [19 lb]
Length	420 mm [16 1/2"]
Blows per minute	1920
Air consumption	12 l/s [25 cfm]
Shank (Hex)	14.7 mm [0.580"]
Shank (Round)	17.3 mm [0.680"]
Retainer type	Quick change



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



HAMMERTIME DEMOLITION HIRE

Rivet Buster

HDH 4608 P

Weight	14 kg [30.9 lb]
Length	584 mm [23"]
Blows per minute	900
Air consumption	21 l/s [44.5 cfm]
Shank	Jumbo
Air inlet (NPTF)	12.7 mm [½"]



HDH 4611 P

Weight	15 kg [33 lb]
Length	660 mm [26"]
Blows per minute	720
Air consumption	21 l/s [44.5 cfm]
Shank	Jumbo
Air inlet (NPTF)	12.7 mm [½"]



HDH 4689

Weight	9.2 kg [20.3 lb]
Length	430 mm [16.9"]
Blows per minute	1500
Riveting capacity	20 mm [0.39"]
Air inlet (NPTF)	12.7 mm [½"]



HDH 4608 D

Weight	14.4 kg [31.7 lb]
Length	600 mm [23.6"]
Blows per minute	900
Air consumption	21 l/s [44.5 cfm]
Shank	Jumbo
Air inlet (NPTF)	12.7 mm [½"]



HDH 4611 D

Weight	15.4 kg [34 lb]
Length	676 mm [26.6"]
Blows per minute	720
Air consumption	21 l/s [44.5 cfm]
Shank	Jumbo
Air inlet (NPTF)	12.7 mm [½"]



RMT 4689 B80

Weight	10.8 kg [23.8 lb]
Length	523 mm [20.6"]
Blows per minute	1200
Riveting capacity	30 mm [1.18"]
Air inlet (NPTF)	12.7 mm [½"]



Clay Digger

HDH CD22 S

Weight	11 kg [24 lb]
Length	495 mm [19.5"]
Blows per minute	1320
Air consumption	21 l/s [45 cfm]
Shank	19 x 82 mm
Retainer type	Screw cap



HDH 222

Weight	12 kg [26 lb]
Length	533 mm [21"]
Blows per minute	1500
Air consumption	19 l/s [40 cfm]
Shank (Hex)	22 x 82.5 mm
Retainer type	Latch



Rotary Drill (Roto Hammer)

HDH 009 S

Weight	4.5 kg [10 lb]
Length	380 mm [15"]
Blows per minute	3420
Air consumption	9 l/s [19 cfm]
Shank (Round)	19 x 95 mm
Retainer type	Quick change



HDH 0014RR

Weight	6.5 kg [14.3 lb]
Length	480 mm [19"]
Blows per minute	2520
Air consumption	22 l/s [47 cfm]
Shank (Hex)	22 x 82.5 mm
Retainer type	Spring



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

Pick Hammer

HDH 09 PS

Weight	10 kg [22 lb]
Length	500 mm [19.7"]
Blows per minute	1800
Air consumption	18.5 l/s [39 cfm]
Shank (Hex)	22 x 82.5 mm
Shank (Round)	25 x 75 mm
Retainer type	Cap



HDH 09 PSKL

Weight	12 kg [26.5 lb]
Length	500 mm [19.7"]
Blows per minute	1800
Air consumption	18.5 l/s [39 cfm]
Shank (Hex)	22 x 82.5 mm
Retainer type	Kick latch



HDH 10 PS

Weight	10 kg [22 lb]
Length	520 mm [20.5"]
Blows per minute	1350
Air consumption	17 l/s [36 cfm]
Shank (Hex)	22 x 82.5 mm
Shank (Round)	25 x 75 mm
Retainer type	Cap



HDH 10 PSKL

Weight	10.5 kg [23 lb]
Length	500 mm [19.7"]
Blows per minute	1350
Air consumption	17 l/s [36 cfm]
Shank (Hex)	22 x 82.5 mm
Retainer type	Kick latch



HDH 12 PS

Weight	10.5 kg [23.1 lb]
Length	550 mm [21.7"]
Blows per minute	1600
Air consumption	21.3 l/s [45 cfm]
Shank (Hex)	22 x 82.5 mm
Shank (Round)	25 x 75 mm
Retainer type	Cap



HDH 12 PSKL

Weight	12.5 kg [27.6 lb]
Length	545 mm [21.5"]
Blows per minute	1600
Air consumption	21.3 l/s [45 cfm]
Shank (Hex)	22 x 82.5 mm
Shank (Round)	25 x 75 mm
Retainer type	Kick-latch



HDH 0122

Weight	11 kg [24 lb]
Length	495 mm [19.5"]
Blows per minute	1320
Air consumption	21 l/s [44.5 cfm]
Shank (Hex)	22 x 82.5 mm
Retainer type	Screw cap



Hydraulic Breaker

HDH manufactures wide range of Hydraulic Rock Breakers which suits all major brand of Mini Excavators, Medium class Excavators, Backhoe Loaders and Skid - Steer Loaders with capacity ranging from 1 to 30 MT. Hyundai, Tata Hitachi, Sany, Kobelco, Volvo, Komatsu, Mahindra, JCB are few of the brands with which our breakers are widely used. There are many more brands of excavator within India and internationally with which our breakers are being used.

Features

- Available from 1 - 23 tons for Mini Excavators, Backhoe Loaders, Skid - Steer Loaders and Medium Class Excavators ;
- Available in backhoe housing and box type silent plus housing ;
- Pure Hydraulic technology gives consistent performance on every blow ;
- Easy service and maintenance ;

Specification	RMT 68	RMT 80	RMT 100	RMT 110	RMT 135	RMT 140
Weight	365 kg [803 lb]	465 kg [1023 lb]	875 kg [1925 lb]	970 kg [2134 lb]	1690 kg [3718 lb]	1850 kg [4070 lb]
Length	1600 mm [63"]	1938 mm [76"]	2317 mm [91"]	2515 mm [99"]	2750 mm [108"]	2860 mm [113"]
Impact power	850 J [626 ft-lb]	1400 J [1031 ft-lb]	2500 J [1842 ft-lb]	3200 J [2360 ft-lb]	5800 J [4274 ft-lb]	6500 J [4790 ft-lb]
Tool diameter	68 mm [2.7"]	80 mm [3.5"]	100 mm [3.9"]	110 mm [4.3"]	135 mm [5.3"]	140 mm [5.5"]
Operating pressure	110 - 130 kg/cm ² [1595 - 1885 PSI]	140 - 160 kg/cm ² [2031 - 2321 PSI]	150 - 170 kg/cm ² [2176 - 2466 PSI]	150 - 170 kg/cm ² [2176 - 2466 PSI]	160 - 180 kg/cm ² [2321 - 2611 PSI]	160 - 180 kg/cm ² [2321 - 2611 PSI]
Optimum oil flow	30 - 45 LPM [7.9 - 11.9 GPM]	45 - 85 LPM [11.9 - 22.5 GPM]	80 - 120 LPM [21.1 - 31.7 GPM]	80 - 120 LPM [21.1 - 31.7 GPM]	120 - 160 LPM [31.7 - 42.2 GPM]	130 - 170 LPM [34.3 - 44.8 GPM]
Blows per minute	500 - 800 BPM	400 - 800 BPM	400 - 700 BPM	400 - 1000 BPM	400 - 600 BPM	400 - 600 BPM
Hose diameter	12 mm [1/2"]	19 mm [3/4"]	19 mm [3/4"]	19 mm [3/4"]	25 mm [1"]	25 mm [1"]
Application carrier	4 - 7 ton	6 - 13 ton	11 - 16 ton	11 - 16 ton	18 - 25 ton	20 - 28 ton



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



HAMMERTIME DEMOLITION HIRE

Sinker Drill

HDH 571

Weight	18 kg [39 lb]
Length	510 mm [20"]
Hole range	28 mm - 34 mm
Hole depth	6 metres [19.6ft]
Blows per minute	2100
Air consumption	39 l/s [83 cfm]
Shank	22 x 108 mm



HDH 658

Weight	24 kg [53 lb]
Length	565 mm [22.2"]
Hole range	27 mm - 40 mm
Hole depth	6 metres [19.6ft]
Blows per minute	2040
Air consumption	58 l/s [123 cfm]
Shank	22 x 108 mm



HDH 12D

Weight	9.8 kg [21.6 lb]
Length	565 mm [22.2"]
Hole range	17 mm - 29 mm
Hole depth	1 metres [3.28ft]
Blows per minute	2580
Air consumption	24 l/s [51 cfm]
Shank	22 x 108 mm



HDH 12T

Weight	11.1 kg [24.5 lb]
Length	505 mm [19.9"]
Hole range	24 - 34 mm [0.94" - 1.34"]
Hole depth	3 metres [10 ft]
Blows per minute	2580
Air consumption	24 l/s [50.9 cfm]
Shank size (Hex)	22 x 108 mm



HDH 330 SD

Weight	25 kg [55 lb]
Length	610 mm [24"]
Hole range (upto)	40 mm [1.57"]
Hole depth (max)	6 metres [19.6ft]
Blows per minute	2400
Air consumption	46 l/s [97 cfm]
Shank	22 x 108 mm



HDH 32A

Weight	24.5 kg [54 lb]
Length	584 mm [23"]
Hole range (upto)	44 mm [1 1/4"]
Hole depth (max)	3 metres [9.8 ft]
Blows per minute	1980
Air consumption	48 l/s [102 cfm]
Shank	22 x 108 mm



HDH 0022

Weight	15 kg [33 lb]
Length	475 mm [18.7"]
Hole range (upto)	40 mm [1.57"]
Hole depth (max)	2.4 metres [7.9 ft]
Blows per minute	2220
Air consumption	22 l/s [47 cfm]
Shank	22 x 82.5 mm
Shank (optional)	22 x 108 mm



HDH 0069

Weight	27.5 kg [59 lb]
Length	610 mm [24"]
Hole range (upto)	60 mm [2.35"]
Hole depth (max)	6 metres [19.6 ft]
Blows per minute	1860
Air consumption	61 l/s [129 cfm]
Shank	22 x 108 mm



Jackleg / Pusherleg Drill

HDH 656W

Weight	22 kg [48.5 lb]
Length	630 mm [24.8"]
Hole range	27 - 41 mm
Hole depth	6 metres [19.6ft]
Blows per minute	2040
Air consumption	48 l/s [102 cfm]
Shank	22 x 108 mm



HDH 330 JLD

Weight	23 kg [50.71 lb]
Length	610 mm [24"]
Blows per minute	2600
Air consumption	57 l/s [120 cfm]
Shank	22 x 108 mm



HDH 16W

Weight	28.5 kg [63 lb]
Length	710 mm [28"]
Hole range	27 - 41 mm
	[1" - 1.63"]
Blows per minute	2340
Air consumption	69 l/s [146 cfm]
Shank	22 x 108 mm



HDH 34W

Weight	33.5 kg [76 lb]
Length	775 mm [30.5"]
Blows per minute	2280
Air consumption	88 l/s [186 cfm]
Hole range	27 - 41mm [1" - 1.63"]
Shank	22 x 108 mm



HDH 94W

Weight	27 kg [59.5 lb]
Length	670 mm [26.40"]
Blows per minute	3300
Air consumption	97 l/s [206 cfm]
Shank	22 x 108 mm



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

Stoper Drill

HDH 46 WS-8

Weight	40 kg [88 lb]
Length retracted	1650 mm [65"]
Length extracted	2620 mm [103"]
Blows per minute	3000
Air consumption	90 l/s [191 cfm]
Shank	22 x 108 mm



HDH 46 WS-6

Weight	39 Kg [86 lb]
Length retracted	1435 mm [56½"]
Length extracted	2205 mm [86.8"]
Blows per minute	3000
Air consumption	90 l/s [191 cfm]
Shank	22 x 108 mm



HDH 330 SL

Weight	39 kg [86 lb]
Length retracted	1700 mm [67"]
Length extracted	2580 mm [102"]
Blows per minute	2900
Air consumption	80 l/s [150 cfm]
Shank	22 x 108 mm



Pneumatic Drifter

HDH 120 F

Weight	70 kg [154 lb]
Length	780 mm [31"]
Air consumption	167 l/s [354 cfm]
Working pressure (max)	7 bar [102 psi]
Piston diameter	120 mm [4.7"]
Piston stroke	65 mm [2½"]
Hole dia (depth) option 1	48 - 57 mm (25 mtr) [2 - 2.24"] (82 ft)
Hole dia (depth) option 2	64 - 75 mm (15 mtr) [2.5 - 3"] (49 ft)
Impact rate	35 Hz
Impact power (max)	7.2 kW
Rotation speed	210 rpm
Drill steel	R32, R38, T38



HDH 120 FZ

Weight	70 kg [154 lb]
Length	780 mm [31"]
Air consumption	167 l/s [354 cfm]
Working pressure (max)	7 bar [102 psi]
Piston diameter	120 mm [4.7"]
Piston stroke	65 mm [2½"]
Hole diameter	48 - 76 mm [2 - 3"]
Impact rate	35 Hz
Impact power (max)	7.2 kW
Rotation speed	210 rpm
Drill steel	R32, R38, T38



Simba Junior

STANDARD

Weight	1200 kg [2640 lb]
Pneumatic drifter	RMT 120F
Hole diameter	48 - 57 mm [1.9 - 2¼"]
Drill rod size	R32
Drill rod length	1.20 metres [4 ft]
Drilling length	25 mtr. max. [82 ft]
Air consumption	189 l/s [400 cfm]
Drilling rate	1 meter in 4 minutes
Feed beam	Screw feed type RMT - 46
Rod catcher	Pneumatic type RSP - 10
Ring size	1500 mm [59"]
Dimension (L x W x H)	1780 x 1550 x 2600 mm [70" x 61" x 102"]
Column bar height	Closed - 2200 mm [87"] Open - 3700 mm [146"]



LATERAL

Weight	1500 kg [3300 lb]
Pneumatic drifter	RMT 120F
Hole diameter	48 - 57 mm [1.9 - 2¼"]
Drill rod size	R32
Drill rod length	1.20 metres [4 ft]
Drilling length	25 mtr. max. [82 ft]
Air consumption	189 l/s [400 cfm]
Drilling rate	1 meter in 4 minutes
Feed beam	Screw feed type RMT - 46
Rod catcher	Pneumatic type RSP - 10
Ring size	1500 mm [59"]
Dimension (L x W x H)	1780 x 1550 x 2600 mm [70" x 61" x 102"]
Column bar height	Closed - 2200 mm [87"] Open - 3700 mm [146"]



MINI

Weight	8 000 kg [1760 lb]
Pneumatic drifter	RMT 120F
Hole diameter	48 - 57 mm [1.9 - 2¼"]
Drill rod size	R32
Drill rod length	1.20 metres [4 ft]
Drilling length	25 mtr. max. [82 ft]
Air consumption	189 l/s [400 cfm]
Drilling rate	1 meter in 4 minutes
Feed beam	Screw feed type RMT - 46
Rod catcher	Pneumatic type RSP - 10
Ring size	1500 mm [59"]
Dimension (L x W x H)	1780 x 1550 x 2600 mm [70" x 61" x 102"]
Column bar height	Closed - 2200 mm [87"] Open - 3700 mm [146"]



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

DTH Hammer

HDH Down the Hole hammers range varies from 2.5 to 12 inches diameter and the DTH bit ranges from 3" to 18" diameter. Premium quality steel combined with quality carbide in the hands of our professional and experienced engineers ensure only the highest quality drilling products. Our hammers yield higher penetration on low fuel consumption.

Even in low air pressure, it gives maximum performance. Our DTH hammers are used for Water well drilling, in mining and quarry as well as in the construction industry. DTH bits are available with different face styles like concave, convex and flat.

	2.5" - 4.5" Hole Dia	4.5" - 5.5" Hole Dia	5.5" - 7" Hole Dia	7" - 12" Hole Dia
Outside Dia	62 mm - 85 mm [2.45" - 3.35"]	98 mm - 107 mm [3.85" - 4.20"]	124 mm - 148 mm [4.90" - 5.9"]	178 mm - 255 mm [7" - 8.85"]
Hole Dia	2.76" - 4.5"	4.5" - 5.5"	5.5" - 7"	7" - 12"
Length	810 mm - 886 mm [31.89" - 35"]	956 mm - 1025 mm [38" - 40"]	994 mm - 1150 mm [39" - 45"]	1172 mm - 1490 mm [46" - 59"]



Wagon Drills

HDH 25 (TH)

Version
Drilling Depth
Hole Diameter
Drill Steel Length
Air Consumption
Feed Type
Feed Beam Length
Travel Length
Feed Force

Top Hammer
20 - 40 meter
48 - 76 mm [2" - 3"]
1.20 Meter, 2.50 & 3 Meter
400 cfm at 7 bar
Chain Drive
5430 mm, 4425 mm, 2825 mm
3940 mm, 2200 mm, 1500 mm
8kN [18 lb]



HDH 25 (DTH)

Version
Drilling Depth
Hole Diameter
Drill Steel Length
Air Consumption
Feed Type
Feed Beam Length
Travel Length
Feed Force

Down the Hole Hammer
40 meter
85 - 130 mm [3.34" - 5.12"]
1.20 Meter, 2.50 & 3 Meter
450 cfm at 10.5 bar
Chain Drive
5430 mm,
4425 mm, 2825 mm
3940 mm,
2200 mm, 1500 mm
8kN [1.8 lb]



Loaders

HDH C310 Cavo / Hopper Loader

Hopper length
Hooper weight
Bucket capacity
Hopper capacity
Air consumption
Air connection
Tire dimension
Hose connection
Ground clearance

270 mm
3050 kg appox
0.13m³ - 4.5 ft³
1m³ - 35.3 ft³ [1mtr]
300 - 350 CFM
40 mm [6 - 7 kg/cm²]
8.25" x 12"
1½ [38 mm]
115 mm



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



HAMMERTIME DEMOLITION HIRE

Jackleg / Pusherleg

HDH 51

Feeding length	1300 mm [51.18"]
Length retracted	1658 mm [65.27"]
Length extracted	2985 mm [117.52"]
Weight	15 Kg [33 lb]
Piston bore	60 mm [2.36"]

HDH 62S

Feeding length	1300 mm [51.18"]
Length retracted	1815 mm [71.45"]
Length extracted	3115 mm [122.63"]
Weight	17 Kg [37 lb]
Piston bore	53 mm [2.08"]

HDH 71

Feeding length	1300 mm [51.18"]
Length retracted	1805 mm [71"]
Length extracted	3105 mm [122.24"]
Weight	14 Kg [31 lb]
Piston bore	70mm [2.75"]

HDH 72D

Feeding length	1300 mm [51"]
Length retracted	1970 mm [77"]
Length extracted	3270 mm [129"]
Weight	19 Kg [42 lb]
Piston bore	70mm [2.75"]

HDH 91RS

Feeding length	1300 mm [51.18"]
Length retracted	1870 mm [73.62"]
Length extracted	3170 mm [124.80"]
Weight	24 Kg [37 lb]
Piston bore	67 mm [2.08"]

Crawler Drill

HDH CW 190

Hole capacity
Drilling max 125 mm dia holes
Mounting
Crawler Mounting
Feed
Chain Feed driven by air motor and gear box
Equipment weight - 2600 kg
Gradeability - 30 Degree



*Ask for separate brochure for more details

Drilling Machine

HDH SLD 100

Dimension of hole	Ø90 to Ø150
Depth of hole - Vertical	30 mtrs.
Length of hole - Horizontal	20 mtrs.
Drill pipe size	Ø 76 mm
Drill pipe length	1.5 mtrs.
Minimum center length of hole from ground	125 mm
Weight (Appx.)	700 kg
Height of rig	3250 mm
Width of rig	600 mm
Rotation unit	4.5 HP
RPM	0 to 50
Feed Unit	4.5 HP
Pull up & down	1500 kg
Air requirement	10cm ³ at 7 bar



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



Wire Saw Machine

Model #	20 HP	40 HP	60 HP
Type machine	Direct drive	Gear box type	Gear box type
Number of RMP		630 m/min	
Water flow requirement		10 ltrs. / min	
Sawing Feed		Variable (Depends on stone hardness)	
Power supply		415 volts AC/3 phase/50HZ	
Installed power required	Total 21 HP	Total 41 HP	Total 61 HP
Main motor power	20HP 960 RPM motor	40HP 1440 RPM motor	60HP 1440 RPM motor
Feed motor power		1 HP D.C. 15000 RPM	
Site of railing	13 feet	20 feet	20 feet
Cable main motor		10 mtr. 1.5 sq mm Three Core (Set)	
Cable D.C. motor		10 mtr. 1.5 sq mm Four Core	
Aluminium Pulley	600 / 625 mm Diameter	790 / 800 mm Diameter	790 / 800 mm Diameter



Lubricator

HDH 30

A must for every single pneumatic tool to increase performance and life.

Tech eqv to

Tank capacity

Weight

Max. working pressure

Hose connection

BLG - 30

1.3 ltrs. [0.34 Gallon]

3 kg [6.6 lb]

20 bar [290 psi]

25 mm [1"]



2 Ltrs. to 30 Ltrs.

High capacity lubricators for drilling rigs and hammers.

Capacity

2 – 30 litre

Working pressure

150 to 350 psi

Air flow maximum

300 to 1400 cfm



Working Tools for Pneumatic Tools – Moil, Chisel, Flat Chisel, Wide Chisel, Asphalt Cutter

HDH manufactures a wide range of Moil, Flat Chisel, Wide Chisel, Asphalt Cutter, Round Blank, in shank size (mm) of 22 x 82.5, 25 x 108, 28 x 160, 32x 160, 14.7, 17.3 etc. in different lengths. We also do Customs manufacturing to suit any kind of Paving Breakers, Chipping Hammers, Pick Hammers and other Pneumatic Tools.



Spare Parts for Construction Tools



Our make spare parts are 100% interchangeable with OEM models of Paving Breakers, Pick Hammers, Chipping Hammers, Rivet Busters, Clay Diggers, Diggers and other tools. Packing of each part is customized to ensure no damage occurs during transit and even if it is stored for a longer period, it does not get rusted. The pricing too is very reasonable.

Spare Parts for Rock Drill



100% interchangeable spares available for most fast moving models of Rock Drills. Most selling spare parts are HDH 658, HDH 571, HDH656W, HDH 12 D etc.

All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



Rock Drilling Tools

Shank Adapter

Manufacturing shank adaptors for various Hydraulic and Pneumatic Drifters. Our Shank Adaptors are manufactured from specially selected alloy steels with heat treatment through carburizing to ensure it withstands the high impact power of drilling. We also do Customs manufacturing as per customer's requirement.

Threads | H112, H114, H90, H92, H64, H55 - Both Right & Left Thread



Coupling Sleeves

Types

- Standard
- Reduction
- Bit Adapters

Dia | From 32 mm to 77 mm
Length | 140 mm to 235 mm
Thread type | R22, R25, R28, R32, R38
T38, T45 & T51



Integral Drill Rod

Features

- Short peened for countering fatigue stress
- Induction brazed for controlled, consistent strong joints
- Chemically treated for anti-corrosion
- Available from 2 feet to 15 feet
- Available in different series



Tapered Rod

Taper	Length	Taper	Length	Taper	Length	SHANK SIZE 22 x 108 m
12'	610	11'	1220	7'	610	
12'	1220	11'	1830	7'	1220	
12'	1830	11'	1980	7'	1830	
12'	2440	11'	2440	7'	1980	
12'	3050	11'	3050	7'	2440	
12'	3660			7'	3050	
				7'	3660	

Extension Rod

Thread Type - R32, R38, T38, T45, T51, ST61
Diameter [D] - 32 mm, 39 mm, 45 mm, 52 mm
Length - 915 mm to 6095 mm



Drifter Rod

Thread Type - R32, R38, T38
Diameter [D] - Hex H32, H35
Length - 3090 mm, 3700 mm, 4305 mm



Top Hammer Bits

TAPER BITS Taper Angle - 7, 11, 12 (Degree)
Diameter [D] - 32, 34, 38, 40 (mm)



THREADED BITS Thread Size - R25, R32, R38, T45, T51, ST61
Diameter [D] - 38, 41, 45, 51, 64, 76, 89, 115, 127, 140 (mm)



RETRACT BITS Thread Size - R38, T45, T51, ST61
Diameter [D] - 45, 64, 76, 89, 102, 115, 127, 140 (mm)



Diameter Available from 2" to 24"

- BR Series**
QL Series
MACH Series
DHD Series
SD Series



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



HAMMERTIME DEMOLITION HIRE

Working Tools for Hydraulic Rock Breaker – Moil Point / Chisel (Cross), Blunt Tool



Our wide range of Hydraulic Hammer Tools are used with most type of heavy duty, boom mounted breaker machines. These are manufactured from high quality steel which is then heat treated in ultra-modern pit-type furnaces to create the hardness, impact strength and durability which is required to face the demanding conditions of quarrying and mining.

Spare Parts for Hydraulic Rock Breaker

HDH manufactures 100% interchangeable spare parts of various models of Rock Breakers. We manufacture and supply spare parts like Tool Pin, Bush Set, Through Bolt, Piston, Seal Kit, Front head of over 250 models of Rock Breakers.



Pumps

HDH 20 - Sump Pump

Power	2.9 kw
Weight	30.5 kg [67 lb]
Min opening needed	230 x 240 mm
Min water depth	22 mm [0.85"]
Max head	27.4 mtr [90 ft]
Air consumption	51 l/s [108 cfm]
Discharge outlet BSP	63.5 mm [2 1/2"]
Air supply hose	25 mm [1"]



HDH 10 - Sump Pump

Power	2.2 kw
Weight	19.5 kg [43 lb]
Min opening needed	210 x 230 mm
Min water depth	22 mm [0.85"]
Max head	30.5 mtr [100 ft]
Air consumption	47 l/s [100 cfm]
Discharge outlet BSP	50 mm [2"]
Air supply hose	19 mm [5/8"]



HDH 77 - Sludge Pump

Weight	69 kg [152 lb]
Min opening needed	584 x 268 mm
Max suction lift	6.1 mtr [20 ft]
Max head	53 mtr [174 ft]
Air consumption	40 l/s [85 cfm]
Discharge inlet	75 mm [3" BSP]
Discharge outlet	64 mm [2 1/2" NPT]
Max solid content	15%



HDH 170 - Diaphragm Pump

Weight	25 kg [55 lb]
Dimension	430 x 305 x 610 mm [17" x 12" x 24"]
Discharge (Minute)	150 - 250 ltr.
Discharge (Hour)	9000 - 15000 ltr.
Air Consumption	33 - 37 5 l/s [70 - 80 cfm]
Air Pressure	4.8 - 5.5 bar [70 - 80 psi]
Suction Size	50 mm [2"]
Suction Lift	3 mtr [10 feet]
Stroke Capacity	60 - 80 / minute



HDH 250 - Diaphragm Pump

Weight	60 kg [132 lb]
Dimension	508 x 430 x 863 mm [20" x 17" x 34"]
Discharge (Minute)	250 - 400 ltr.
Discharge (Hour)	15000 - 24000 ltr.
Air Consumption	42 - 47 l/s [90 - 100 cfm]
Air Pressure	5.5 - 6.2 bar [80 - 90 psi]
Suction Size	75 mm [3"]
Suction Lift	3 mtr [10 feet]
Stroke Capacity	90 - 100 / minute



Cement Injection Pump

HDH 545 RNS

Total Weight	22 kg [48.5 lb]
Total Height	1115 mm [44"]
Width & Length	610 x 200 mm [24" x 8"]
Air Pressure Required	42 - 47 l/s at 4.8 - 5.5 bar
Total Head Capacity	90 - 100 cfm at 70 - 80 psi
Pressured Delivered	3 - 20 meter [10 - 60 ft]
Flow Rate	500 psi (Maximum)
Mixture Free Speed of Motor	15 - 20 ltr/minute (Maximum)
	300 RPM



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

Die Grinders

HDH DG 113

Collect size	6 mm [0.24"]
Free speed	22,000 rpm
Weight	0.57 kg [1.25 lb]
Air consumption	1.89 l/s [4 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	175 mm [6.90"]



HDH DG 313

Collect size	6 mm [0.24"]
Free speed	35,000 rpm
Weight	0.6 kg [1.32 lb]
Air consumption	1.89 l/s [4 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	140 mm [5.5"]



HDH DG 413

Collect size	6 mm [0.24"]
Free speed	30,000 rpm
Weight	0.80 kg [1.76 lb]
Air consumption	1.89 l/s [4 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	155 mm [6.10"]



HDH DG 513

Collect size	6 mm [1/4"]
Free speed	30,000 rpm
Weight	0.93 kg [2 lb]
Air consumption	1.89 l/s [4 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6 mm [1/4"]
Length	165 mm [6.5"]



HDH DG 613

Collect size	6 mm [1/4"]
Free speed	28,000 rpm
Weight	1.2 kg [2.65 lb]
Air consumption	2.36 l/s [5 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6 mm [1/4"]
Length	185 mm [7.25"]



HDH DG 713

Collect size	3 mm [1/8"]
Free speed	54,000 rpm
Weight	0.11 kg [0.25 lb]
Air consumption	2.36 l/s [5 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6 mm [1/4"]
Length	155 mm [6.10"]



HDH DG 913

Collect size	6 mm [1/4"]
Free speed	25,000 rpm
Weight	0.33 kg [0.7 lb]
Air consumption	2.36 l/s [5 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6 mm [1/4"]
Length	121 mm [4 1/4"]



HDH DG 123

Collect size	6 mm [1/4"]
Free speed	25,000 rpm
Weight	0.7 kg [1.55 lb]
Air consumption	2.36 l/s [5 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6 mm [1/4"]
Length	235 mm [9 1/4"]



HDH DG 223

Collect size	6 mm [1/4"]
Free speed	21,000 rpm
Weight	1.8 kg [3.90 lb]
Air consumption	14.15 l/s [30 cfm]
Air pressure	6 bar [90 psi]
Air inlet	9.5 mm [3/8"]
Length	317 mm [12 1/8"]



HDH DG 023

Collect size	6 mm [1/4"]
Free speed	22,000 rpm
Weight	0.5 kg [1.25 lb]
Air consumption	1.89 l/s [4 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	160 mm [6"]



Angle Grinders

HDH AG 115

Wheel capacity	100 mm [4"]
Free speed	11000 rpm
Weight	1.8 kg [4 lb]
Air consumption	2.8 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	230 mm [9"]



HDH AG A215

Wheel capacity	125 mm [5"]
Free speed	11000 rpm
Weight	1.8 kg [4 lb]
Air consumption	2.8 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	230 mm [9"]
Operation	Lever Type



HDH AG 315

Wheel capacity	177 mm [7"]
Free speed	7000 rpm
Weight	3.2 kg [7 lb]
Air consumption	4.25 l/s [9 cfm]
Air pressure	6 bar [90 psi]
Air inlet	9.5 mm [3/8"]
Length	350 mm [13 8/16"]
Operation	Lever Type



HDH AG 415

Wheel capacity	177 mm [7"]
Free speed	7600 rpm
Weight	3.1 kg [6.8 lb]
Air consumption	4.25 l/s [9 cfm]
Air pressure	6 bar [90 psi]
Air inlet	6.35 mm [1/4"]
Length	260 mm [10 25/32"]
Operation	Lever Type



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.

www.hammertimedemolition.com
dilaan@monolit.co.za



HAMMERTIME DEMOLITION HIRE

Drilling Machines

HDH DM 187

Type	Angle drilling
Shank Size	10 mm [3/8"]
Air consumption	2.83 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet thread	6.35 mm [1/4"]
Speed	1900 rpm
Weight	0.96 kg [2.1 lb]
Length	190 mm [7.5"]



HDH DM 287

Type	Straight type
Shank Size	10 mm [3/8"]
Air consumption	2.83 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet thread	6 mm [1/4"]
Speed	2600 rpm
Weight	0.96 kg [2.12 lb]
Length	203 mm [8"]



HDH DM 387

Type	Gun type
Shank Size	10 mm [3/8"]
Air consumption	2.83 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet thread	6 mm [1/4"]
Speed	1800 rpm
Weight	1.1 kg [2.43 lb]
Length	180 mm [7"]



HDH DM 487

Type	Gun type
Shank Size	13 mm [5/8"]
Air consumption	2.83 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Air inlet thread	6.35 mm [1/4"]
Speed	1800 rpm
Weight	0.9 kg [1.98 lb]
Length	200 mm [7.9"]



Impact Wrench

HDH IW 612

Square drive	12.7 mm [5/8"]
Free speed	7000 rpm
Torque	576 Nm [425 ft lb]
Air consumption	2.83 l/s [6 cfm]
Air pressure	6 bar [90 psi]
Bolt capacity	M16 mm
Air inlet (BSP)	6.35 mm [1/4"]
Weight	2.4 kg [5.29 lb]
Length	190 mm [7.5"]



HDH IW 812

Square drive	19 mm [5/8"]
Free speed	4200 rpm
Torque	677 Nm [500 ft lb]
Air consumption	3.80 l/s [8 cfm]
Air pressure	6 bar [90 psi]
Bolt capacity	M25 mm
Air inlet (BSP)	6.35 mm [1/4"]
Weight	5 kg [11 lb]
Length	245 mm [9.65"]



HDH IW 122

Square drive	25 mm [1"]
Free speed	3000 rpm
Torque	4000 Nm [2950 ft lb]
Air consumption	11 l/s [23 cfm]
Air pressure	6 bar [90 psi]
Bolt capacity	M50 mm
Air inlet	12.7 mm [5/8"]
Weight	16 kg [35.2 lb]
Length	660 mm [26"]



Riveters

HDH R 116

Weight (without snap)	1.12 kg [2.47 lb]
Length	150 mm [5.90"]
Stroke Length	41 mm [1.61"]
Air Inlet Thread	6.35 mm [1/4"]
Air Pressure	6 bar [90 psi]
Air Consumption	1.89 l/s [4 cfm]
No. of Blows	4500
Riveting Capacity	5 - 8 mm [0.20" - 0.31"]



HDH R 216

Weight (without snap)	1.55 kg [3.41 lb]
Length	190 mm [7.50"]
Stroke Length	66 mm [2.60"]
Air Inlet Thread	6.35 mm [1/4"]
Air Pressure	6 bar [90 psi]
Air Consumption	2.36 l/s [5 cfm]
No. of Blows	3500
Riveting Capacity	5 - 8 mm [0.20" - 0.31"]



Pop Riveters

HDH PR 349

Riveting Capacity	2.4 - 4.8 mm [1/16" - 5/16"]
Air Pressure	6 bar [90 psi]
Air Consumption	2 l/s [4.2 cfm]
Air Inlet	6.35 mm [1/4"]
Net Weight	1.3 kg [2.8 lb]



HDH PR 549

Riveting Capacity	2.4 - 4.8 mm [1/16" - 5/16"]
Air Pressure	6 bar [90 psi]
Air Consumption	2 l/s [4.2 cfm]
Air Inlet	6.35 mm [1/4"]
Net Weight	1.4 kg [3.1 lb]





HAMMERTIME DEMOLITION HIRE

Angle Type Sanders

HDH S 182

Wheel capacity	75 mm [3"]
Free speed	16000 rpm
Air pressure	6 bar [90 psi]
Air consumption	1.89 l/s [4 cfm]
Air inlet	6.35 mm [1/4"]
Length	177 mm [7"]
Approx weight	0.8 kgs [1.76 lb]



HDH PS 1P0

Wheel capacity	150 mm [6"]
Free speed	10000 rpm
Air pressure	6 bar [90 psi]
Air consumption	2.8 l/s [6 cfm]
Air inlet	6.35 mm [1/4"]
Length	165 mm [6.5"]
Approx weight	0.95 kgs [2.1 lb]

Palm Sanders

HDH PS 2P0

Wheel capacity	150 mm [6"]
Free speed	10000 rpm
Air pressure	6 bar [90 psi]
Air consumption	2.8 l/s [6 cfm]
Air inlet	6.35 mm [1/4"]
Length	165 mm [6.5"]
Approx weight	0.8 kgs [1.75 lb]



Belt Sanders

HDH BS 010

Belt size	10 x 330 mm [0.40 x 13"]
Free speed	16000 rpm
Air pressure	6 bar [90 psi]
Air consumption	2.8 l/s [6 cfm]
Air inlet	6.35 mm [1/4"]
Length	260 mm [10.25"]
Weight	0.9 kg [2 lb]



HDH BS 210

Belt size	12.7 x 610 mm [0.50 x 24"]
Free speed	16000 rpm
Air pressure	6 bar [90 psi]
Air consumption	2.8 l/s [6 cfm]
Air inlet	6.35 mm [1/4"]
Length	470 mm [18.50"]
Weight	1.1 kg [2.4 lb]



HDH BS 020

Belt size	20 x 520 mm [0.80 x 20.50"]
Free speed	16000 rpm
Air pressure	6 bar [90 psi]
Air consumption	2.8 l/s [6 cfm]
Air inlet	6.35 mm [1/4"]
Length	340 mm [13.40"]
Weight	1.2 kg [2.65 lb]



Rammers

HDH R 115

Stroke	102 mm [4"]
Length	460 mm [18"]
Weight	4.2 kgs [9.25 lb]
Butt size (Rubber)	63.5 mm [2.5"]
B.P.M	850 [±5%]
Air pressure	6 bar [90 psi]
Air consumption	7 l/s [15 cfm]
Air inlet	9.5 mm [3/8"]



HDH R 215

Stroke	203 mm [8"]
Length	1156 mm [45.5"]
Weight	10.9 kgs [24 lb]
Butt size (Rubber)	63.5 mm [2.5"]
B.P.M	800 [±5%]
Air pressure	6 bar [90 psi]
Air consumption	11.8 l/s [25 cfm]
Air inlet	12.7 mm [5/8"]



Chippers

HDH C 127

Air pressure	6 bar [90 psi]
Air consumption	1.9 l/s [4 cfm]
Weight	1.1 kgs [2.4 lb]
Length	150 mm [5.9"]
Stroke length	41 mm [1.6"]
Air inlet thread	7 mm [1/4"]
Blows per min	4500



HDH C 227

Air pressure	6 bar [90 psi]
Air consumption	2.36 l/s [5 cfm]
Weight	1.5 kgs [3.3 lb]
Length	190 mm [7.5"]
Stroke length	66 mm [2.60"]
Air inlet thread	7 mm [1/4"]
Blows per min	3500



Nutserts (Nut Inserts)

HDH N 118

Time cycle	7.5 - 12 / sec
Air pressure	6 bar [90 psi]
Thread size	M4,M5,M6
Length	280 mm [11"]
Weight	1.5 kgs [3.30 lb]
Air inlet	6 mm [1/4"]
Air consumption	1.89 l/s [4 cfm]



HDH N 218

Time cycle	7.5 - 12 / sec
Air pressure	6 bar [90 psi]
Thread size	M8 & M10
Length	280 mm [11"]
Weight	1.5 kgs [3.30 lb]
Air inlet	6 mm [1/4"]
Air consumption	1.89 l/s [4 cfm]



HDH SD 277

Torque	10 nm [7.5 ft lbs]
Free speed	12000 rpm
Hex shank	6 mm [1/4"]
Screw capacity	M5 mm
Length	195 mm [7.7"]
Air inlet	6.35 mm [1/4"]
Air pressure	6 bar [90 psi]
Air consumption	1.9 l/s [4 cfm]
Weight	0.7 kg [1.50 lb]



HDH SD 677

Torque	12 Nm [8.85 ft lbs]
Free speed	12000 rpm
Hex shank	6 mm [1/4"]
Screw capacity	M5 mm
Length	167 mm [6.6"]
Air consumption	1.89 l/s [4 cfm]
Air inlet	6.35 mm [1/4"]
Air pressure	6 bar [90 psi]
Weight	0.8 kg [1.75 lb]



All manufacturer's names, numbers, product descriptions and/or part numbers are used for reference purposes only.



📞 : +27 81 501 0807

✉️ : dilaan@monolit.co.za

🌐 : hammertimedemolition.com